

08 Strips & Profiles > Connect In One Length Range 24V

7820L/W



Flexible LED light strip, with SMD2216 LEDs, 60LEDs/meter, 4,8W/meter. Supplied in 15 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 10cm (6-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads




Dimensions




Gallery



Accessories



7822



7824

Related items





20030

Physical Specification

Item Group	08 Strips & Profiles
Family	Connect In One Length Range 24V
Order Code	7820L/W
Shape	Rectangular
Length	15000mm
Width	8mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

Electrical Characteristics

Fitting

Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	4,8W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2216
LED Brand	Refond
LED Number	60LEDs/m
F Mark	

Illumination Data

Colour Temperature	3000K
Lumen Output	375lm/m
Light Efficiency	78,12lm/W
CRI	90
Illumination Diagram	

Packing Info

Box Length	25cm
Box Width	25cm
Box Height	2cm
Box Weight	0,36kg
Pcs/Carton	40
Barcode	5291889054436
HS Code	9405409989

Certification & Warranty

Warranty	5 Years
Weee Directive	Yes