

09 LED Strips & Profiles>The Ultra Slim Range 24V

CE

7823/EW



Slim Flexible LED light strip, with SMD2216 LEDs, 140LEDs/meter, 9,6W/meter.Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 5cm (7-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Dimensions

Cut every 5cm (7-LED segment)

Gallery

£);}

Downloads

IES



Related items



20030

Physical Specification

Item Group

09 LED Strips & Profiles

Family	The Ultra Slim Range 24V
Order Code	7823/EW
Shape	Rectangular
Length	5m
Width	5mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

Electrical Characteristics

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	9,6W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2216
LED Brand	Refond
LED Number	140Leds/m

Illumination Data

Lumen Output	768lm/m
Light Efficiency	80lm/W
CRI	90
Illumination Diagram	

Packing Info

24cm
21,5cm
2cm
0,18kg
40
5291889048794
9405409989

Energy Label



Energy Class

F

Certification & Warranty

Warranty	5 Years
Weee Directive	Yes