



Slim Flexible LED light strip, with SMD2216 LEDs, 140LEDs/meter, 9,6W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 5cm (7-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Related items




20030

Physical Specification


Family	The Ultra Slim Range 24V
Order Code	7823/W
Shape	Rectangular
Length	5m
Width	5mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

## Electrical Characteristics

### Fitting

Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	9,6W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2216
LED Brand	Refond
LED Number	140Leds/m


## Illumination Data

Colour Temperature	3000K
Lumen Output	864lm/m
Light Efficiency	90lm/W
CRI	90
Illumination Diagram	

## Packing Info

Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Box Weight	0,17kg
Pcs/Carton	40
Carton Length	51cm
Carton Width	45cm
Carton Height	24cm
Carton Weight	6,9Kg
Barcode	5291889048787
HS Code	9405409989

## Energy Label



## Certification & Warranty

Warranty	5 Years
Weee Directive	Yes