

## 09 LED Strips & Profiles>The RGB & RGBW Strips 24V

# 7830/RGB



RGB flexible LED light strip, with SMD5050 LEDs, 60LEDs/meter, 14,4W/meter.Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 10cm (6-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



## Downloads







#### **Dimensions**

Cut every 10cm (6-LED segment)



## Related items







7832/RGB



7834/RGB



89100LP

### **Physical Specification**

Item Group	09 LED Strips & Profiles
Family	The RGB & RGBW Strips 24V
Order Code	7830/RGB
Shape	Rectangular
Length	5m
Width	10mm
Surface Ceiling	Yes

Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

# Electrical Characteristics

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	14,4W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 5050
LED Brand	Refond
LED Number	60Leds/m

# Illumination Data

Colour Temperature RGB

Illumination Diagram

KGB

Packing Info

Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Box Weight	0,2kg
Pcs/Carton	40
Barcode	5291889017691
HS Code	9405409989

Warranty	5 Years
Weee Directive	Yes

Certification & Warranty