

# 09 LED Strips & Profiles>The Ultra Slim Range 24V

CE

# 7833/EW



Slim Flexible LED light strip, with SMD2110 LEDs, 196LEDs/meter, 14,4W/meter.Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 3,5cm (7-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.

Dimensions

Cut every 3,5cm (7-LED segment)

#### Gallery

£);}

Downloads

IES



**Related items** 



20030

Physical Specification

Item Group

09 LED Strips & Profiles

Family	The Ultra Slim Range 24V
Order Code	7833/EW
Shape	Rectangular
Length	5m
Width	4mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

### **Electrical Characteristics**

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	14,4W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2110
LED Brand	Refond
LED Number	196Leds/m


## Illumination Data

Lumen Output	1160lm/m
Light Efficiency	80,55lm/W
CRI	90
Illumination Diagram	

# Packing Info

Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Pcs/Carton	40
Barcode	5291889058830
HS Code	9405409989

# Energy Label



Energy Class

F

# Certification & Warranty

Warranty	5 Years
Weee Directive	Yes