

09 LED Strips & Profiles>The 230V IP65 Range

7860/D



230V Waterproof LED strip 9W/m, IP65.

Supplied in 50m rolls.

Can be cut every 1m.

Requires power supply order code 7860P.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Gallery



Must be ordered separately



7860P

Accessories











7860F

7860L

7860R

| Thysical opecinication | |
|----------------------------|--------------------------|
| Item Group | 09 LED Strips & Profiles |
| Family | The 230V IP65 Range |
| Order Code | 7860/D |
| Shape | Rectangular |
| Length | 50000mm |
| Width | 15mm |
| Surface Ceiling | Yes |
| Surface Wall | Yes |
| Surface Floor/Ground | Yes |
| Indoor | Yes |
| Outdoor | Yes |
| | |
| Electrical Characteristics | |
| | |
| Gear | External-Included |
| | |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 9W/m |
| IP Rating | IP65 |
| Light Source | LED built in |
| Dimmable | Yes |
| Dimmer type | Triac |
| F Mark | F |
| | |
| Fitting | |
| Safety Class | |
| Power(Watts) | 9W/m |

| IP Rating | IP65 |
|-----------------------|---------------|
| Light Source | LED built in |
| LED Type | SMD 3528 |
| LED Brand | Epistar |
| | |
| Gear | |
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 450W |
| Power Factor | 0,9 |
| IP Rating | IP65 |
| Safety Class | |
| Brand | 0 |
| Protection | 0 |
| | |
| Illumination Data | |
| Colour Toron eveture | 00001/ |
| Colour Temperature | 900lm/m |
| Light Efficiency | 100lm/W |
| Light Efficiency CRI | 80 |
| | 00 |
| Illumination Diagram | |
| | |
| Packing Info | |
| Pcs/Carton | 50 |
| Barcode | 5291889030911 |
| HS Code | 9405403990 |
| | |

| Warranty | 2 Years |
|------------------|------------|
| Average Lifetime | 30000hours |
| Weee Directive | Yes |

Certification & Warranty