

08 Strips & Profiles>The 19,2W/m Indoor 24V

7870/W



Flexible LED light strip, with SMD2216 LEDs, 238LEDs/meter, 19,2W/meter.Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 2,95cm (7-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Dimensions

Cut every 2,95cm (7-LED segment)

Downloads



Gallery



Physical Specification

Item Group	08 Strips & Profiles
Family	The 19,2W/m Indoor 24V
Order Code	7870/W
Shape	Rectangular
Length	5000mm
Width	10mm
Surface Ceiling	Yes

Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

Electrical Characteristics

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	19,2W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2216
LED Brand	Refond
LED Number	238LEDs/m
F Mark	F

Illumination Data

Colour Temperature	3000K
Lumen Output	1728lm/m
Light Efficiency	90lm/W
CRI	90
Illumination Diagram	

Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Box Weight	0,22kg

Pcs/Carton	40
Barcode	5291889031918
HS Code	9405409989

Energy Label

ENERGY OVELIGHT LIG P370/W A B C D E F G 19 kWh /1000h E 19 kWh /1000h E 19 kWh /2015		
Energy Class	F	

Certification & Warranty	
Warranty	5 Years
Weee Directive	Yes