




LIPA CL

LED Outdoor surface-mounted ceiling light, IP54, white, 3000/4000K

SLV LIPA robust, water-protected surface-mounted solution. Round wall and ceiling light made from aluminium. Thanks to its IP54 protection class it is suitable for outdoor use. The opal illuminated area has an LED light source beneath it which can be switched between warm and cool white, and is enclosed by the painted housing. The luminaire comes in several colour versions and is connected directly to the 230V mains supply thanks to its built-in LED driver.



TECHNICAL DATA

Item no.:	1001855
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Height	6.3 cm
Diameter	28 cm
Net weight	1.953 kg
Gross weight	2.394 kg
IP Code	IP 54
Safety class	I
Impact resistance class	IK05
Impact resistance	0,7 Joule
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	10
Wattage	21 W
Lumen	1600 lm
Colour temperature	3000/4000 Kelvin
Beam angle	120 °
Color	white
LXXBXX data	L70B50

Light Source

916401	
--------	---

Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
BIG WHITE Page	690