



SUPROS PD

Indoor LED pendant, round, white, 3000K, 60° reflector, CRI90, 2600lm

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.

TECHNICAL DATA

Item no.:	1003276
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	750mA
Pendant length	200 cm
Height	18.5 cm
Diameter	12.7 cm
Net weight	1.645 kg
Gross weight	1.759 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Wattage	31 W
Lumen	2600 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	90
LXXBXX data	L70B50
Ambient temperature	25 °C
BIG WHITE Page	148

Light Source

791822	
--------	---

Accessories

114102	REFLECTOR , for SU-PROS, 20°, incl. glass and fixing ring
114104	REFLECTOR , for SU-PROS, 40°, incl. glass and fixing ring

