



SUPROS

Indoor LED recessed ceiling light white round 3000K $60^\circ\,\text{CRI90}$ 2600Im

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.

TECHNICAL DATA

Item no.:	1003300
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	750mA
Height	11 cm
Diameter	16.5 cm
Installation diameter	15.3 cm
Installation depth	10.7 cm
Net weight	0.94 kg
Gross weight	1.074 kg
IP Code	IP 20
Safety class	
Assembly	Recessed
Assembly details	Ceiling
Wattage	31 W
Lumen	2600 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	90
LXXBXX data	L70B50
Ambient temperature	25 °C
BIG WHITE Page	384



Light Source

791822	A E
Accessories	
114102	REFLECTOR , for SU- PROS, 20°, incl. glass and fixing ring
114104	REFLECTOR , for SU- PROS, 40°, incl. glass and fixing ring

