




SUPROS MOVE

Indoor LED recessed ceiling light black round 4000K
60° CRI90 2700lm

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



TECHNICAL DATA

Item no.:	1003311
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	750mA
Height	17 cm
Diameter	19.5 cm
Installation diameter	18 cm
Installation depth	11.5 cm
Net weight	1.516 kg
Gross weight	1.69 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Wattage	31 W
Lumen	2700 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	black
CRI	90
LXXBXX data	L70B50
Ambient temperature	25 °C
BIG WHITE Page	386

Light Source

791825	
--------	---

Accessories

114102	REFLECTOR , for SU-PROS, 20°, incl. glass and fixing ring
114104	REFLECTOR , for SU-PROS, 40°, incl. glass and fixing ring

