






NOYAPD PHASE

Indoor LED pendant light black CCT switch 2700/3000K

The NOYA pendant light looks more stylish than ever indoors: in its proven elegant SLV design, it will impress you all round with a high colour rendering index (CRI>90) and a light colour (2700/3000K) that can be flexibly adjusted using the CCT switch on the top of the light. With its elongated slender shape, delicate colour details and high-quality appearance, it creates a harmonious lighting ambience in any home, as well as over tables and counters in hotels, restaurants or even cafés, for a harmonious lighting ambience. The light colour should only be selected when switched off.



TECHNICAL DATA

Primary nominal voltage 220-240V ~50/60Hz mA/V Secondary power / secondary voltage 700mA Length 120 cm Pendant length 150 cm Width 4.2 cm Height 4 cm Net weight 2.724 kg Gross weight 4.229 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Dimmable Yes Dimming technology trailing edge	
ge 120 cm Pendant length 150 cm Width 4.2 cm Height 4 cm Net weight 2.724 kg Gross weight 4.229 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Dimmable Yes	
Pendant length 150 cm Width 4.2 cm Height 4 cm Net weight 2.724 kg Gross weight 4.229 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Dimmable Yes	
Width 4.2 cm Height 4 cm Net weight 2.724 kg Gross weight 4.229 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Dimmable Yes	
Height 4 cm Net weight 2.724 kg Gross weight 4.229 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Dimmable Yes	
Net weight 2.724 kg Gross weight 4.229 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Dimmable Yes	
Gross weight 4.229 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Dimmable Yes	
IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Dimmable Yes	
Safety class Assembly Surface Assembly details Ceiling Dimmable Yes	
Assembly Surface Assembly details Ceiling Dimmable Yes	
Assembly details Ceiling Dimmable Yes	
Dimmable Yes	
Dimming technology trailing edge	
Wattage 32 W	
Lumen 2025 lm	
Colour temperature 2700/3000 Kelvin	
Beam angle 115 °	
Color black	
CRI 90	
LXXBXX data L70B50	





Light Source

916317	A E

Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	142



