




NUMINOS® PD PHASE M

Indoor LED pendant light black/black 4000K 60°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you provide a thousand lighting design options. This also includes NUMI-NOS® PD PHASE M, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 20.1 watts, luminous flux of 2060 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| | T |
|-------------------------------------|----------------------------|
| Item no.: | 1004260 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500mA |
| Pendant length | 250 cm |
| Height | 18.5 cm |
| Diameter | 8.5 cm |
| Net weight | 0.955 kg |
| Gross weight | 1.202 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling, Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Wattage | 20.1 W |
| Lumen | 2060 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 60 ° |
| Color | black |
| CRI | 90 |
| UGR≤ | 25 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 90 |
| | ! |







Light Source

| 791825 | |
|-------------|-------------------------------|
| Accessories | |
| 1006168 | NUMINOS® M , white front ring |