






## **OCULUS CL**

## Indoor LED wall and ceiling mounted light black DIM-TO-WARM 2000-3000K

With a high colour rendering index (CRI>90) and the option of dim-to-warm dimming for an especially warm light (2000-3000K), every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting.



## **TECHNICAL DATA**

Item no.:	1004666
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	250mA
Height	9 cm
Diameter	9 cm
Net weight	0.597 kg
Gross weight	0.748 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	11 W
Lumen	780 lm
Colour temperature	2000-3000 Kelvin
Beam angle	100°
Color	black
CRI	90
LXXBXX data	L70B50
Minimum ambient temperature	-20 °C
	<del>,</del>





## Light Source

		_
916608	â F	N

Maximum ambient temperature	50 °C
BIG WHITE Page	280



