




NUMINOS® MOVE S

white recessed ceiling light, 3000K 40°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® MOVE S recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that simple installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.:	1005350
Number of different light outlets	1
Secondary power / secondary voltage	250mA
Height	6.35 cm
Diameter	10 cm
Installation diameter	9 cm
Installation depth	8.5 cm
Net weight	0.19 kg
Gross weight	0.203 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	8.6 W
Lumen	730 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR ≤	19



Light Source

791815	
--------	---

Accessories

1004055	LED driver , 6.5-10W 250mA PHASE
1004058	LED driver , 6.5-10W 250mA
1004067	LED driver , 15W 250mA DALI
1004786	NUMINOS® S , diffuser Ellipse
1004787	NUMINOS® S , diffuser Prisma
1004788	NUMINOS® S , diffuser Frosted
1004789	NUMINOS® S , diffuser Wabe
1006139	Numinos® S Mounting Frame , round 160/100mm black
1006140	Numinos® S Mounting Frame , round 160/100mm white
1006141	Numinos® S Mounting Frame , square 160/100mm black
1006142	Numinos® S Mounting Frame , square 160/100mm white

LXXBXX data	L80B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	41

