




WORKLIGHT DALI

black pendant light, 57W 4000K 80°

As a consistent further development of our WORKLIGHT series, this WORKLIGHT is an office pendant light for screen-based workstations, equipped with state-of-the-art technology and highly efficient, high-output LEDs and of course $UGR \leq 19$. The light can be controlled via DALI. The WORKLIGHT is ready for direct connection to a 230V mains power supply thanks to its pre-installed driver and supply cable. This light contains integrated LED light bulbs.





TECHNICAL DATA

Item no.:	1005395
Number of different light outlets	2
Primary nominal voltage	200-240V ~50/60Hz mA/V
Secondary power / secondary voltage	1550mA
Length	120 cm
Pendant length	250 cm
Width	26 cm
Height	3 cm
Net weight	5.787 kg
Gross weight	7.953 kg
IP Code	IP 20
Safety class	I
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Wattage	57 W
Lumen	5000 lm
Colour temperature	4000 Kelvin
Beam angle	80 °



Light Source

916322	
916564	

Color	black
CRI	80
UGR \leq	19
LXXBXX data	L80B10
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
BIG WHITE Page	774

