




## **NUMINOS® XS**

white / black recessed ceiling light, 2700K  $40^{\circ}$ 

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## **TECHNICAL DATA**

| Item no.:                           | 1005511       |
|-------------------------------------|---------------|
| Secondary power / secondary voltage | 200mA         |
| Height                              | 4.5 cm        |
| Diameter                            | 6.5 cm        |
| Installation diameter               | 5.5 cm        |
| Installation depth                  | 11 cm         |
| Net weight                          | 0.09 kg       |
| Gross weight                        | 0.096 kg      |
| IP Code                             | IP 20 / IP 44 |
| Safety class                        | Ш             |
| Impact resistance class             | IK02          |
| Impact resistance                   | 0,2 Joule     |
| Assembly                            | Recessed      |
| Assembly details                    | Ceiling       |
| Wattage                             | 7 W           |
| Lumen                               | 620 lm        |
| Colour temperature                  | 2700 Kelvin   |
| Beam angle                          | 40 °          |
| Color                               | white         |
| CRI                                 | 90            |
| UGR≤                                | 22            |
| LXXBXX data                         | L80B50        |
|                                     | -             |





## Light Source

| 798300      | â F   |
|-------------|---|
| Accessories |   |
| 1005609     | LED Driver , 200mA 10W<br>PHASE, Quick Connector              |
| 1005610     | LED Driver , 200mA 10-<br>W, Quick Connector                  |
| 1005611     | LED Driver , 200mA<br>13,5W DALI dimmable,<br>Quick Connector |
| 1005612     | NUMINOS® XS , diffuser  |
| 1005613     | NUMINOS® XS , transparent diffuser                            |
| 1005614     | NUMINOS® XS , frosted diffuser                                |
| 1005615     | NUMINOS® XS , black diffuser                                  |

| Minimum ambient temperature | -20 °C |
|-----------------------------|--------|
| Maximum ambient temperature | 40 °C  |
| BIG WHITE Page              | 29     |



