




NUMINOS® XS

white recessed ceiling light, 3000K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.:	1005533
Secondary power / secondary voltage	200mA
Height	4.5 cm
Diameter	6.5 cm
Installation diameter	5.5 cm
Installation depth	11 cm
Net weight	0.09 kg
Gross weight	0.096 kg
IP Code	IP 20 / IP 44
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	7 W
Lumen	720 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L80B50



Light Source

798303	
--------	---

Accessories

1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005610	LED Driver , 200mA 10-W, Quick Connector
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1005612	NUMINOS® XS , diffuser
1005613	NUMINOS® XS , transparent diffuser
1005614	NUMINOS® XS , frosted diffuser
1005615	NUMINOS® XS , black diffuser

Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	29

