





## SUPROS 78

recessed fitting, LED, 3000K, round, white, 60° lens, 9W

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



## TECHNICAL DATA

Item no.:	116311
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	250mA
Height	7.5 cm
Diameter	11.8 cm
Installation diameter	10.8 cm
Installation depth	8 cm
Net weight	0.438 kg
Gross weight	0.507 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	12 W
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	96

## Light Source

916364	
--------	---

LXXBXX data	L70B50
-------------	--------

## Accessories

BIG WHITE Page	382
----------------	-----

116302	LENS , for SUPROS 78, 20°
116304	LENS , for SUPROS 78, 40°

