




## NUMINOS® DL S

Indoor LED recessed ceiling light black/black 3000K  
 20° gimballed, rotating and pivoting, including leaf  
 springs

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® DL S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 8.6 watts, luminous flux of 690 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

Item no.:	1003793
Number of different light outlets	1
Secondary power / secondary voltage	250mA
Height	5.2 cm
Diameter	8 cm
Installation diameter	6.8 cm
Installation depth	5.5 cm
Net weight	0.16 kg
Gross weight	0.2 kg
IP Code	IP 20 / IP 44
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	8.6 W
Lumen	690 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	19