



NUMINOS® DL L

Indoor LED recessed ceiling light white/white 4000K 55°

The NUMINOS light system from SLV skilfully combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® DLL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 25.41 watts, a luminous flux of 2450 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety or



TECHNICAL DATA

| Item no.: | 1003980 |
|--|---------------|
| Number of different light outlets | 1 |
| Secondary power / secondary volta- ge | 700mA |
| Height | 8.5 cm |
| Diameter | 13 cm |
| Installation diameter | 11.7 cm |
| Installation depth | 9 cm |
| Net weight | 0.465 kg |
| Gross weight | 0.525 kg |
| IP Code | IP 20 / IP 44 |
| Safety class | III |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 25.41 W |
| Lumen | 2450 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 55 ° |
| Color | white |
| CRI | 90 |
| UGR≤ | 22 |