



3~ NUMINOS® PHASE S

3 phase system light white/black 4000K 36°

The NUMINOS light system from SLV skilfully combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the 3--NUMINOS® PHASE S 3-phase system light LED, which convinces with best workmanship and light quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1100 lumens, colour temperature of 400 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.:	1004095
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	250mA
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm
Net weight	0.5 kg
Gross weight	0.8 kg
Safety class	1
Assembly details	Track Ceiling, Track Wall
Dimmable	Yes
Dimming technology	trailing edge
Wattage	10.42 W
Lumen	1100 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR≤	16
LXXBXX data	L80B50
BIG WHITE Page	62