



## NUMINOS® PD PHASE S

Indoor LED recessed ceiling light black/black 4000K  $24^{\circ}$ 

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® PD PHASE S, which impresses as a pendant light with the best workmanship and lighting quality. In this way, you can create high-quality limination of larger areas or use the spotlight for selective lighting. The pendant light has a power consumption of 10.42 watts, a luminous flux of 1100 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMI-NOS® from SLV?



## **TECHNICAL DATA**

Item no.:	1004162
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	250mA
Pendant length	250 cm
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.69 kg
Gross weight	0.929 kg
Safety class	1
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	10.42 W
Lumen	1100 lm
Colour temperature	4000 Kelvin
Beam angle	24 °
Color	black
CRI	90
UGR≤	16
LXXBXX data	L80B50
BIG WHITE Page	88