



## **NUMINOS® PD PHASE S**

Indoor LED pendant light white/black 4000K 24°

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® PD PHASE S, which impresses as a pendant light with the best work-manship and lighting quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1100 lumens, colour temperature of 400 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## **TECHNICAL DATA**

Item no.:	1004166
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	250mA
Pendant length	250 cm
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.691 kg
Gross weight	0.923 kg
Safety class	1
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	10.42 W
Lumen	1100 lm
Colour temperature	4000 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR≤	16
LXXBXX data	L80B50
BIG WHITE Page	88