




NUMINOS® PD PHASE S

Indoor LED pendant light white/black 4000K 60°

The NUMINOS light system from SLV skillfully combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® PD PHASE S pendant light, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The pendant light has a power consumption of 10.42 watts, a luminous flux of 1100 lumens, a colour temperature of 4000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.:	1004168
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	250mA
Pendant length	250 cm
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.697 kg
Gross weight	0.931 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	10.42 W
Lumen	1100 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50
BIG WHITE Page	88