



## NUMINOS® CL PHASE M

Indoor LED surface ceiling light black/black 2700K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® CL PHASE M indoor celling—mounted light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed celling light convinces with a power consumption of 20.1 watts, luminous flux of 1935 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV — modular diversity awalts you.



## TECHNICAL DATA

Item no.:	1004219
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	500mA
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.68 kg
Gross weight	0.93 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	1935 lm
Colour temperature	2700 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR≤	16
LXXBXX data	L80B50
BIG WHITE Page	82