



NUMINOS® PD PHASE M

Indoor LED pendant light white/black 2700K 24°

The NLMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NLMINOS® PD PHASE M pendant light, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality litimination of larger areas. The recessed celling light convinces with a power consumption of 20.1 watts, luminous flux of 1925 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS @ Form SLV?



TECHNICAL DATA

Item no.:	1004246
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	500mA
Pendant length	250 cm
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.94 kg
Gross weight	1.006 kg
Safety class	1
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	1925 lm
Colour temperature	2700 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR≤	16
LXXBXX data	L80B50
BIG WHITE Page	90