




3~ NUMINOS® PHASE L

3 phase system light black/black 4000K 24°

The NUMINOS light system from SLV skillfully combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the 3~ NUMINOS® PHASE L 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2675 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.:	1004282
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700mA
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.07 kg
Gross weight	1.4 kg
Safety class	I
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	28 W
Lumen	2675 lm
Colour temperature	4000 Kelvin
Beam angle	24 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50
BIG WHITE Page	66