



NUMINOS® CL PHASE L

Indoor LED surface ceiling light black/black 4000K 24°

The NUMINOS light system from SLV skilfully combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® CL PHASE L indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2675 lumens, colour temperature of 4000 Kellvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMI-NOS® from SLV?



TECHNICAL DATA

Item no.:	1004330
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	700mA
Height	21.3 cm
Diameter	10 cm
Net weight	0.89 kg
Gross weight	0.952 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	28 W
Lumen	2675 lm
Colour temperature	4000 Kelvin
Beam angle	24 °
Color	black
CRI	90
UGR≤	19
LXXBXX data	L80B50
BIG WHITE Page	84