




NUMINOS® PD PHASE L

Indoor LED pendant light black/black 3000K 60°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® PD PHASE L pendant light, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The pendant light has a power consumption of 28 watts, a luminous flux of 2400 lumens, a colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.:	1004348
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700mA
Pendant length	250 cm
Height	21.3 cm
Diameter	10 cm
Net weight	1.257 kg
Gross weight	1.555 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	28 W
Lumen	2400 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
BIG WHITE Page	92