





## 3~ NUMINOS® DALIS

## 3 phase system light black/black 3000K 36°

The NLMINOS light system from SLV skilfully combines function, design and technology. The diverse downlights and spotlights make a thousand lighting design options possible. Like with the 3- NLMINOS® DALI S 3-phase system light LED, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1020 Lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NLMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

Item no.:	1004371
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	250mA
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm
Net weight	0.56 kg
Gross weight	0.85 kg
Safety class	1
Assembly details	Track Ceiling, Track Wall
Dimmable	Yes
Dimming technology	DALI
Wattage	10.42 W
Lumen	1020 lm
Colour temperature	3000 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR≤	13
LXXBXX data	L80B50
BIG WHITE Page	62