




3~ NUMINOS® DALI M

3 phase system light black/black 4000K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Like with the 3~ NUMINOS® DALI M 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 2060 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1004476 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500mA |
| Length | 18.5 cm |
| Height | 16.5 cm |
| Diameter | 8.5 cm |
| Net weight | 0.83 kg |
| Gross weight | 1.13 kg |
| Safety class | I |
| Assembly details | Track Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Wattage | 20.1 W |
| Lumen | 2060 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 60 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 25 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 64 |