



NUMINOS® PD DALI M

Indoor LED pendant light white/black 4000K 60°

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® PD DALI M, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The pendant light can convince with a power consumption of 20.1 watts, luminous flux of 2060 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

| Item no.: | 1004552 |
|--|---------------------------|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary volta- ge | 500mA |
| Pendant length | 250 cm |
| Height | 18.5 cm |
| Diameter | 8.5 cm |
| Net weight | 1.08 kg |
| Gross weight | 1.156 kg |
| Safety class | 1 |
| Assembly | Surface |
| Assembly details | Ceiling,Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | DALI |
| Wattage | 20.1 W |
| Lumen | 2060 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 60 ° |
| Color | white |
| CRI | 90 |
| UGR≤ | 25 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 90 |