



3~ NUMINOS® DALIL

3 phase system light white/black 4000K 60°

Design, technology and function in perfection: NLMINOS is the light system from SLV that combines everything. The diverse downlights and spotlights make a thousand lighting design options possible. Like with the 3 – NUMINOS® DALI L3-phase system light LED, which impresses with is high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed celling light cominces with a power consumption of 28 watts, luminous flux of 2715 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity wardis you.



TECHNICAL DATA

Item no.:	1004576
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	700mA
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.115 kg
Gross weight	1.45 kg
Safety class	1
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	DALI
Wattage	28 W
Lumen	2715 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR≤	22
LXXBXX data	L80B50
BIG WHITE Page	66