



NUMINOS® XL PHASE

white / black pendant light, 36W 3000K 24 $^{\circ}$

The NUMINOS light system from SLV combines technology, design and functionality like no other. The different downlights and spotlights make a thousand lighting design options possible. Like with the NUMINOS® XL PHASE pendant light, which impresses with its high-quality work-manship and light. In this way, you can create high-quality liumination of larger areas or use the spotlight for selective lighting. The pendant light has a power consumption of 36 watts, a luminous flux of 3530 lumens, a colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.:	1005714
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	900mA
Pendant length	250 cm
Height	25.8 cm
Diameter	12 cm
Net weight	1.745 kg
Gross weight	1.867 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	36 W
Lumen	3530 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR≤	19
BIG WHITE Page	95