





DASAR PROJECTOR

outdoor floodlight, LED, 3000K, IP68, stainless steel 316, 12-24V, 7W

The accessible high-voltage inground light DASAR Projector LED PRO impresses with its stainless steel screen and glass cover in a partial satin finish. Its IP 68 protection class makes it ideal for outdoor use. The rotatable and pivoting GU10 fitting allows flexible alignment of the light cone. And last but not least, it is the LED lifespan of 25,000 that makes the outdoor ground spike light LED a long-lasting companion. Experience light with SLV – your innovalive partner for all kinds of outdoor lights for 40 years.



TECHNICAL DATA

Item no.:	233570
Primary nominal voltage	12-24V mA/V
Length	7.2 cm
Width	10 cm
Height	10.8 cm
Net weight	1.337 kg
Gross weight	1.423 kg
IP Code	IP 68
Safety class	III
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc., Ground, Ground with Acc., Wall, Wall with Acc.
Wattage	6.5 W
Lumen	520 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	stainless steel
CRI	80
LXXBXX data	L70B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	598
	+