

PRODUCT CATALOG

# 20 Series Exit Device



Experience a safer and more open world

# **Table of Contents**



Features, Applications and UL Fire Door Ratings	3
2727 Vertical Rod Type Exit Device	4
2828 Rim Type Exit Device	5
20 Series Trims	6
Alternate Strikes and Shim Kits	7
Mullions and Door Kits	8-9
Mechanical and Cylinder Options	10
Cylinder Options	11
Ordering Information, Rail Sizes and Finishes	12
Architectural Specifications and How To Order	13

# **WARNING**

This product can expose you to lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov.

# On The Cover

 $\frac{\langle \cdot \rangle}{\langle \cdot \rangle}$  SARGENT 2828 Rim Exit Device with EN Finish

# Features, Applications and **UL Fire Door Ratings**




# **APPLICATIONS**


# **Features**

- Rugged exit device in surface vertical rod and rim designs
- Chassis mounted unit construction assures easy installation and maintenance
- Tapered push rail and angled covers
- Steel endcaps and covers
- Up to five functions with a variety of
- All exit devices meet ANSI/BHMA Standard 156.3, Grade 1
- **UL** Listed
- UL Listed to Canadian safety
- Available as Fire Exit Hardware (12-)

# Single Door



Vertical Rod Type 2727 Surface applied 2 / 1 point lock. Rim Type 2828 Surface application.



Pairs of Doors without Mullion

Vertical Rod Type 2727 - 2 Each

Surface applied 2 / 1 point locking both


doors. Each door active. Do not use an over-

Vertical Rod Type 2727 - 1 Each Rim Type 2828 - 1 Each Both devices are surface applied. A

coordinator is required.

lapping astragal.

### Pairs of Doors with 980 Mullion



Two independent active doors with full double door opening when required.

### **Maximum Door Openings & UL Fire Door Ratings**

For available functions and outside trim, see charts for regular exit devices

• = Available			UL Fire Door Rating				
Application & Type	Regular Design	Maximum Door Opening	(A) 3 Hour	(B) 1 1/2 Hour	(B) 1 1/2 Hour	(D) 1/2 Hour	(E) 3/4 Hour
Single Doors Rim Type	12-2828	4'0" X 8'0" (1219mm X 2438mm)	•	•	•	•	•
Pair of Doors Two Surface Mounted Vertical Rod Type - Swinging in same direction	*12-2727 x *12-2727	8'0" X 8'0" (2438mm X 2438mm)	•	•	•	•	•
Two Rim Type with 12-980 Mullion	12-2828 x 12-2828	8'0" X 8'0" (2438mm X 2438mm)	•	•	•	•	•
Two Surface Mounted Vertical Rod Type - Swinging in opposite directions	12-2727 x 12-2727	8'0" X 8'0" (2438mm X 2438mm)	•	•	•	•	•

Note: Please contact door manufacturer for specifications regarding fire door construction

\* Limited for fire doors listed by UL for this use. NFPA requires an astragal on 3 hour applications. Vertical rod application will not work with astragal.


 $^{\wedge}$  Thermal pins required, 2 pins per set, 1 per door.

Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and Sargent Manufacturing Company makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

# 2727 Vertical Rod Type Exit Device



# **SPECIFICATIONS**




The 2727 Multi-function SVR Exit Device is the perfect stocking device.

- 6 functions determined by trim selected
- Device & trim sold separately; easy to mix and match
- 4 available trim designs

Order as an 2727 followed by rail size, opening, AFF and finish


# **Minimum Stile Requirements**

Double Door – with two vertical rod type exit devices




# 646 Top Strike

- Standard for both Panic & Fire (12-) Hardware with or without bottom rod
- Surface applied to frame
- Black nylon coated




# 655 Bottom Strike (Fire Rated)

- Standard for 12-
- Stainless steel
- Black nylon coated




# 624 Bottom Strike (Panic)

- Standard for 2727
- Applied to surface of floor or to a flat threshold
- Black nylon coated



# 2828 Rim Type Exit Device






The 2828 Multi-function Rim Exit Device is the perfect stocking device.

- 7 functions determined by trim selected
- Device & trim sold separately; easy to mix and match
- 4 available trim designs


Order as an 2828 followed by rail size and finish

For Doors	1-3/4" (44) thick standard. 4-1/2" (114mm) minimum stile width required for single or double door application using standard 649 strike
Outside Trim Thumbpiece Trims	28 Series Lever & Rose Trims, GTB/HTB Pulls & Plates, OB Knob Trims & Thumbpiece Trims
Mounting	Furnished standard with wood and machine screws Available with through-bolts and mortise nuts
Cover	Steel
Chassis	Nonferrous alloy
Rail Assembly	Roll formed steel
End Cap	Steel
Hand	Non handed
Latchbolt	Stainless steel 3/4" (19mm) throw
Strike	649 packed standard
Dogging Feature	Allen-type key furnished standard (non fire rated devices only)
Fire Exit Hardware	See chart page 3
Finish	EB, ED, EN, EP, EAB


# 649 Strike



# Minimum Stile Requirements



# **Minimum Stile Requirements**



- Surface applied
- Standard & fire rated
- Strikes are black nylon coated

# 20 Series Trims



The trim function determines the function of the exit device. All 28 Series trims work with all 20 Series Exit Devices, except where noted. Note: All trims and exit devices are ordered and packaged separately

# 28 SERIES LEVER & ROSE TRIM FOR 2727/2828 SERIES EXIT DEVICES

### **Lever & Rose Trim**





- For 1-3/4" (44mm) doors only
- Functions available for 04, 06, 10, 13, 15, BSP, WSP
- Not handed
- Finishes: 03, 04, 10, 10B, 10BE, 20D & 26D
- Lever designs available: "L", "B", "P"

To order specify 28 followed by the function Trim will not retrofit on devices purchased prior to 2000. Consult factory.

(K, N, D, C or L), the rose (L), the lever (L, B or P) and finish Example: 28-K-LL x 26D



# 28-K-LL **Night Latch** Key in lever

retracts latchbolt.

04 Function For 3828 only (ANSI 03)



# 28-N-LL **Night Latch**

Lever operates only when key is in cylinder and turned.

06 Function (ANSI 09)



# 28-D-LL **Dummy**

Lever rigid at all times & no outside function.

10 Function (ANSI 02)



# 28-C-LL **Entrance**

Key in lever locks or unlocks lever.

13 Function (ANSI 08)



# 28-L-LL **Passage**

Latchbolt operated by lever.

No Cylinder 15 Function (ANSI 14)

# 28 SERIES GTB/HTB PULLS & PLATES FOR 2727/2828 SERIES EXIT DEVICES





• Trim ordered separately.

Example: 814-HTB x EN

• Finishes: EN, EB, ED, EP & EAB • For cylinder operation only with no trim,



810-GTB 802-GTB

• For 1-3/4" (44mm) doors standard

• Through-bolted with 3 mortise nuts

• Pulls project 1-1/2" (38mm) from door face

(Specify 2828 x 34 rim cylinder x finish) To order specify: trim design and finish

• GTB Design Trim will cover a 161 cutout






814-HTB



814-HTB **Night Latch** 

Outside by pull and key. (2828 only)


04 Function (ANSI 03)



# 810-GTB **Exit Only with Pull**

Outside pull when push bar is locked down.

10 Function (ANSI 02)



# 802-GTB **Exit Only**

Blank plate to cover 161 cutout.

10 Function

(ANSI 01)

# 28 SERIES OB KNOB TRIM FOR 2727/2828 SERIES EXIT DEVICES



- For 1-3/4" (44mm) doors only
- Functions available for 04, 13 and 15
- Non-handed
- Finishes: 26D

To order specify 28 followed by the function (K, C or L), the rose (O), the knob (B) and finish Example: 28-K-OB x 26D



28-K-OB

Night Latch

Key in knob





# 28-C-OB **Entrance**

retracts latchbolt. 2828 only 04 Function (ANSI 03)



# Key in knob

locks or unlocks knob. 13 Function (ANSI 08)



# 28-L-OB Passage

Latchbolts operated by knob. No Cylinder 15 Function

(ANSI 14)

# 28 SERIES THUMBPIECE TRIM FOR 2727/2828 SERIES EXIT DEVICES



- Finishes: EN, EB, ED, EP & EAB
- \*1 3/4" Door Only

866-TP Key locks or unlocks thumbpiece (63)

814-TP Kev retracts latchbolt (2828 ONLY) (04)

To order specify: trim design and finish Example: 866-TP x EN


# Copyright © 2003-2025, SARGENT Manufacturing Company. All rights reserved. Reproduction in whole or in part without the express wind permission of SARGENT Manufacturing Company is prohibited. Patent pending and/or patent www.assaabloydss.com/patents.

# Alternate Strikes and Shim Kits




# **ALTERNATE STRIKES**

# 613 Strike (Alternative for 2828)




Half mortised. Nylon coating on face plate only. Minimum stile 4". When ordered separately, specify finish.

### 644 Strike (Alternative for 2828)




Surface applied. For use on pair of doors without mullion. Specify outside finish when ordered separately.

# 642 Strike (Alternative for 2828)



Full mortised dimension "L" equals door thickness plus 1/2" (13mm).

# 653 Bottom Strike (Alternate for 12-2727)




Available on order for 12-2727. For use with 1/2" (13mm) high threshold. Cut threshold to fit strike. Stainless steel. Furnished with expansion shields.

# **GLASS BEAD SHIM KITS**

# 558 for 2828 and 12-2828 Exit Devices 559 for 2727 and 12-2727 Exit Devices

Note: When ordering shim kits for exits with outside trim, spindle length, thumbpiece length and through bolt length must be increased accordingly.

(2 pieces 1/8" shim supplied. 1/4" total.)



# THROUGH BOLT (TB) APPLICATIONS

Device	Door Thickness	*Ordering Number
2727	1-3/4" (44mm) 2-1/4" (57mm)	28-2031 28-2032
12-2727	1-3/4" (44mm) 2-1/4" (57mm)	28-2078 28-2088
2828 & 12-2828	1-3/4" (44mm) 2-1/4" (57mm)	28-2024 28-2025

<sup>\*</sup>Specify finish

Through bolts and mortise nuts are furnished in a pack along with the appropriate instruction sheet for device ordered.

To order through bolts and mortise nuts with an exit device, add suffix TB to trim pack.

# Example: 2727 x TB x EN


Available finishes: EB, EN, ED, EAB

To order through bolt and mortise nut packs separately, see chart above.



Product	Top Rod Kit ++	Bottom Rod Kit +++
2700+	672T	672B

- + Finish Information Required
- ++ Door Height & Rail Location Required
- +++ Rail Location Required



08/25


# Mullions and Door Kits



### 980 Removable Mullion


980 Extruded Aluminum (prime coat) 980A Aluminum (US28) Consists of:

- Mullion
- 511 Top Retainer
- 502 Bottom Retainer
- 86" (2184mm) stock size; 120" (3000mm) available



# 507 Adapter for Narrow **Transom Bars**

- Available with 980 and 980A
- Required when soffit is 1-1/4" (32mm) to 2" (51mm) wide



### 12-980 Mullion (96" maximum) For 12-3828

2" x 3" Channel Iron. Malleable iron top and bottom retainers.

- 86" (2184mm) stock size; 120" (3000mm)
- Fire rating is valid only up to 96" (2438mm)
- Mullions longer than 86" (2184mm) must be ordered as 12- option x 120" (3000mm length and cut to size in the field.

# Top Retainer Shim Kit - 601



# 543 Stock Hollow Metal Door Kit


Kit consists of a 649 Strike Shim, a 161F Lock Front Filler, and a 86S Strike Filler for applying a 3828 Series Exit Device on doors prepared with Fed. Type 161 cutouts, and frames prepared for ANSI A115-2 Strikes. The 649 strike shim is 1/8" (3mm) thick and is used to obtain the correct distance between the exit device case and the 649 surface applied strike, when the stop is 1/2" (13mm) high.



Note: For complete Listing of available mullions, see the 80 Series Catalog

### L980 Lockable Mullion

- Aluminum Prime Coat
- Specify: "L980A"Anodized Aluminum Specify: "L980A x10B" for 313AN to match



- 86" (2184mm) stock size
- 120" (3000mm) available
- Standard #41 cylinder (1-1/8")
- Cylinder options: Signature, XC-, Schlage Keyways SC- & SE- available
- Wall Mount Kit 98-2578
- Top Ret Pack 98-2526
- Bottom Ret Pack 98-2525
- Cylinder Kit must be ordered separately (980C1)

# **SM980S Split Mullion**

- Steel
- Panic Rated
- Gray Paint finish
- Hassle-free transportation with a 30% smaller packaging size
- 96" (2438 mm ) Stock Size

# SML980S Lockable **Split Mullion**

- Steel
- Panic Rated
- Gray Paint finish
- Hassle-free transportation with a 30% smaller packaging
- 96" (2438 mm ) Stock Size
- #41 cylinder standard (#42 & #43 available)
- Cylinder options: Signature, XC-, Schlage

# Keyways SC- & SE- available

- Top Retainer Shim Kit 601
- Cylinder Kit must be ordered separate
- 980C1 Available in 32D and 108 finish)

# **SMEL980**

- Steel
- For use with monitor or electric strikes
- Quick-Connect wiring supplied
- 96" (2438 mm ) Stock Size
- Requires a #46 cylinder
- Top Retainer Shim Kit 601
- Not available in 12- option
- Cylinder Kit must be ordered separate (980C2 - Available in 32D and 108 finish)

# Mullions and Door Kits



# 12-L980 Lockable Mullion

- Steel
- Fire rated for 8'0" x 8'0" (2438mm x 2438mm) paired openings
- 86" (2184mm) Stock Size
- Fire rating is valid only up to 96" (2438mm)
- Mullions longer than 86"(2184mm) must be ordered as 12- option x 120" (3000mm) length and cut to size in the field.
- #41 cylinder standard
- Cylinder options: Signature, XC-, Schlage Keyways SC- & SE- available
- Top Retainer Shim Kit 601
- Cylinder Kit must be ordered separately (980C1)

### **EL980 Electric Lockable Mullion**

- Steel
- For use with monitor or electric strikes
- Quick-Connect wiring supplied
- 86" (2184mm) stock size
- 120" (3000mm) availableRequires a #46 cylinder
- Top Retainer Shim Kit 601
- Not available in 12- option
- Cylinder Kit must be ordered separately (980C2)

# Mullion Accessories RK980

Latchbolt assembly retrofit kit with top and bottom retainers for 980 mullion

# Retainer Packs

Product #	Description
98-2526	Top Ret. pack for L980
98-2525	Bottom Ret. pack for L980
98-2558	Top Ret. pack for 12-L980
98-2556	Bottom Ret. pack for 12-L980, EL980,SMEL980
98-2559	Top Ret. pack for EL980, SMEL980

08/25

# Mechanical and Cylinder Options



# **Mechanical Options:**

Note: Mechanical Options are available for Exit Devices only

Fire Rated	Fire Rated UL Fire Label Exit hardware (not available with 16- & HK-)	
Dogging Options	LD-	Less Dogging (Non Fire Rated Devices Only)

# **Cylinder Options:**

Note: Cylinder Options are available for 16- Exit Devices and 04, 06 & 13 function trims

	Code	Description	Lever Trim	Knob Trim	GTB-HTG- Thumbpc Trim	Rail - 16-Cyl Dogging
	DG1-	SARGENT Degree Key System Level 1 (bump resistant with patented keys)	Х	Х	X	Х
	DG1-21-	Degree Level 1 Construction Master Keying	X	X	X	X
	DG1-60-	Degree Level 1 Removable Disposable Construction Core	X		X	X
	DG1-63-	Degree Level 1 Removable Core	X		X	X
	DG1-64-	Degree Level 1 Removable Construction Keyed LFIC	X		X	X
	DG2-	SARGENT Degree Key System Level 2 (geographically exclusive; bump and pick resistant)	X	Х	X	Х
Degree Key	DG2-21-	Degree Level 2 Construction Master Keying	X	X	X	X
System	DG2-60-	Degree Level 2 Removable Disposable Construction Core	X		X	X
	DG2-63-	Degree Level 2 Removable Core	X		X	X
	DG2-64-	Degree Level 2 Removable Construction Keyed LFIC	X		X	X
	DG3-	SARGENT Degree Key System Level 3 (geographically exclusive; UL437 certified; bump and pick resistant)	Х	Х	X	Х
	DG3-21-	Degree Level 3 Construction Master Keying	X	Х	X	X
	DG3-60-	Degree Level 3 Removable Disposable Construction Core	X		X	X
	DG3-63-	Degree Level 3 Removable Core	X		X	X
	DG3-64-	Degree Level 3 Removable Construction Keyed LFIC	X		X	Χ
	10-	SARGENT Signature Key System	Х	Х	X	Х
Signature Key System	10-21-	SARGENT Signature Construction Key System (Lost Ball)	X	X	X	Х
System	10-63	SARGENT Signature LFIC (Removable Core) Cylinder	X		X	X

Note: For cylinder options not shown, please contact factory for availability

Note: For V-10 Cylinders and information, contact ASSA

# Cylinder Options



	Code	Description	Lever Trim	Knob Trim	GTB-HTG- Thumbpc Trim
11- & 11-21-	11-	XC Key System (not available with other Key systems unless specified)	X	Х	X
XC- Key System	11-21-	XC- Construction Key System (Lost Ball)	Χ	Х	X
11-60 to 11-64	11-60	Hardware to accept XC- Permanent LFIC (Removable Core), Disposable plastic Core- provided	Х		Х
=XC- Large Format	11-63	Hardware provided with XC- LFIC (Removable Core) Cylinder - (includes masterkeying, grand masterkeying)	Х		Х
Interchangeable Core	11-64	Hardware provided with Keyed construction core to accept XC- LFIC (Removable) Permanent Core (ordered separately)	Χ		X
	11-70-7P	Lock to accept XC- SFIC (7-Pin) XC- Permanent Cores, plastic disposable core provided	Χ		Х
XC-	11-72-7P	Lock to accept XC- SFIC (7-Pin Keyed Construction Core provided) cylinder Permanent Core ordered separately	Χ		Х
Interchangeable Cores	11-73-7P	Lock supplied with XC- Small Format 7-Pin interchangeable core (includes masterkeying, grand masterkeying)	X		Х
	11-65-73-7P	Lock provided to accept XC- Uncombinated 7-Pin SFIC (Permanent) Core - (packed loose)	Χ		X
	60	Hardware to accept SARGENT Permanent LFIC (Removable Core), Disposable plastic Core provided (Permanent Cores ordered separately)	Χ		X
Large Format Interchangeable	63	Hardware provided with LFIC (Removable Core) Cylinder - (includes masterkeying, grand masterkeying)	Χ		Х
Core	64	Hardware provided with Keyed construction core to accept LFIC (Removable) Permanent Core (ordered separately)	Х		Х
	70	Lock to accept 6- or 7-Pin SFIC Permanent Cores, plastic disposable core provided	Χ		X
	72	Lock to accept 6- or 7-Pin SFIC (Keyed Construction Core provided) Cylinder (Permanent Core ordered separately)	X		X
	73	Lock supplied with 6-Pin SFIC (Includes masterkeying, grand masterkeying)	Χ		X
Interchangeable Cores	65-73	Lock provided to accept Uncombinated 6-Pin SFIC (Permanent) Core - (packed loose for field keying)	Х		X
	65-73-7P	Lock provided to accept Uncombinated 7-Pin SFIC (Permanent) Core - (packed loose for field keying)	X		X
	73-7P	Lock supplied with Small Format 7-Pin Interchangeable Core (includes masterkeying, grand masterkeying)	X		Х
	80	Lock to accept Keso and Keso F1 cylinders - no cylinders provided			X
	81	Cyl to accept Keso and Keso F1 - Removable cores - no core provided			X
Keso &	82	Lock provided with SARGENT Keso Security Cylinder			X
Keso F1	F1-82	Lock provided with SARGENT Keso F1 Security Cylinder (Patented)			X
	83	SARGENT Keso Security Removable Core Cylinder (for existing systems only)			X
	84	SARGENT Keso Security Removable Construction Core Cylinder			X
Construction Key Systems	21-	SARGENT Lost Ball Construction Keying for Conventional, XC and Signature Series (N/A with 63- or 73-)	Χ	Х	X
Bump Resistant	BR-	Bump Resistant Cylinder (Available with Conventional & Conventional XC Cylinders only)		Х	Х
Less Cylinder	LC-	Less Cylinder		Х	X
	SC-	Schlage C keyway cylinder, 0 bitted	Х	Х	X
Schlage	SE-	Schlage E keyway cylinder, 0 bitted	Χ	Х	Х
Keyways	SF-	L lever to accept Schlage large format interchangable core (supplied less core, tailpiece included)	Χ		

Note: For cylinder options not shown, please contact factory for availability

Note: For V-10 cylinders and information, contact ASSA

08/25

# Ordering Information, Rail Sizes and Finishes



### **Check List for Ordering**

Indicate the following door and frame information:

- Single doors, or pair of doors with mullion, or pair of doors without mullion
- Door and frame material
- Dimensions:
  - Door opening width
  - Stile width
  - Door thickness
  - Stop height

### Example: Single Door x Hollow Metal Frame 36" x 5" x 2-1/4" x 1/2"

- If Vertical Rod Devices also indicate:
  - Mounting height
  - Door opening height
  - Threshold height
  - If no threshold is used, so state
  - Unless threshold information is indicated, exit device will be furnished for use without threshold

  - Mullion stock size is 96" (2438mm); 120" (3000mm) available In ordering templates for hollow metal doors and/or frames, state job name on template order. Give template order number or template numbers on hardware order



Е	For doors	24" through 32"	61cm through 81cm
F	For doors	33" through 36"	82cm through 91cm
G	For doors	43" through 48"	109cm through 122cm


# Finishes available with Lever & Rose Trim and OB Knob Trim


SARGENT Designation	ANSI/BHMA Designation	Finish Description
03	605	Bright brass, clear coated
04	606	Satin brass, clear coated
10	612	Satin bronze, clear coated
10B	613	Dark oxidized satin bronze, oil rubbed
10BE	613E	Dark oxidized satin bronze, equivalent
20D	624	Statuary bronze dark powder coated
26D	626	Satin chromium plated
BSP	_	Black Suede Powder Coat
WSP	_	White Suede Powder Coat


# Finishes available with Exit Devices, GTB Trims & Thumbpiece Trim

SARGENT Designation ANSI/BHMA Designation	ANSI/BHMA Designation Finish Description	Finish Description SARGENT Designation
EB	690	Sprayed bronze enamel or polyester powder coated to match finish 10B
ED	693	Sprayed black enamel or polyester powder coated to match finish 20D
EN	689	Sprayed aluminum enamel or polyester powder coated
EP	691	Sprayed bronze enamel or polyester powder coated to match finish 10
EAB	696	Brass enamel or polyester powder coated to be used with brass finishes

<sup>\*\*</sup> AFF: Above Finish Floor or Threshold; Required information for 3727 Devices. Standard mounting height 41" (104mm) above finished floor to centerline of device or 38" (965mm) above finished floor to centerline of device for elementary schools.







### **Packaging**

Product	Avg. WT	Case
Exit with trim	15 lbs.	1 ea
980 mullion	18 lbs.	1 ea
12-980 mullion	40 lbs.	1 ea

# Architectural Specifications and How To Order



# HOW TO ORDER 2727/2828 MULTI-FUNCTION EXIT DEVICES:

Specify the following for 2727 Devices:						
Options	Series	Rail	Opening	AFF	Finish	
11	2727	F	84"	41"	EN	

Specify the following for 2828 Devices:				
Options	Series	Rail	Finish	
11-12-	2828	F	EN	

- All trims and functions listed on this page, work with 2727 & 2828 Exit Devices, except where noted
- Available Options listed on page 10

# HOW TO ORDER TRIM FOR 2727 & 2828 EXIT DEVICES (EXIT DEVICE SOLD SEPARATELY)

# Example:

11-	28-C-LL		26D	
Options	Available Trim & Function Designation		Available Finishes	
Available	Lever & Rose Trim		Lever & Rose Finishes	
Options See Page 10	28-K-LL (04 Function)	28-C-LL (13 Function)		
	28-N-LL (06 Function)	28-L-LL (15 Function)	03, 04, 10, 10B, 10BE, 20D, 26D	
	28-D-LL (10 Function)			
	GTB/HTB Trims & Pulls		GTB/HTB Finishes	
	814-HTB (04 Function)		EN, ED, EAB, EB, EP	
	802-GTB (10 Function) Exit Only			
	810-GTB (10 Function) Pull			
	OB Knob Trim		OB Knob Finish	
	28-K-OB (04 Function)		26D	
	28-C-OB (13 Function)			
	28-L-OB (15 Function)			
	Thumbpiece Trim		Thumbpiece Finishes	
	814-TP (04 Function)		EN, ED, EAB, EB, EP	
	866-TP (63 Function)			

# SUGGESTED ARCHITECT'S SPECIFICATIONS

- All exit devices shall be of touch bar design and be operative over 2/3 of the door's clear opening width
- All exit devices must be listed under "Panic Hardware" in the Accident Equipment List of Underwriter's Laboratories, Inc. Where labeled
  doors are used as exits, they must be equipped with labeled Fire Exit Hardware
- All springs shall be of stainless steel
- All exit devices shall be of chassis mounted unit construction with removable cover

The ASSA ABLOY Group is the global leader in access solutions. Every day, we help billions of people experience a more open world.

ASSA ABLOY Opening Solutions leads the development within door openings and products for access solutions in homes, businesses and institutions. Our offering includes doors, frames, door and window hardware, mechanical and smart locks, access control and service.



SARGENT Manufacturing Company 100 Sargent Drive New Haven, CT 06511 USA 800-727-5477 www.sargentlock.com

Founded in the early 1800s, SARGENT® is a market leader in locksets, cylinders, door closers, exit devices, electromechanical products and access control systems for new construction, renovation, and replacement applications. The company's customer base includes commercial construction, institutional, and industrial markets.

Copyright © 2003-2025, SARGENT Manufacturing Company. All rights reserved. Reproduction in whole or in part without the express written permission of SARGENT Manufacturing Company is prohibited. Patent pending and/or patent www.assaabloydss.com/patents.