

Energy Efficient Steel Stiffened Door

Increase Building Energy Efficiency in Any Weather Condition



With energy prices continually increasing and commercial buildings consuming almost 40% of energy usage in North America, Ceco Door remains committed to providing maximum thermal resistant solutions. The Trio-E door is steel stiffened for strength, but has achieved an operable U-Factor of 0.34 which is better than most other steel stiffened doors currently available on the market today. Many building owners spend millions of dollars a year on energy bills and the Trio-E represents a chance for them to realize significant savings on a new or retrofit project.

Green

- One of the lowest operable U-Factor in the industry for a steel stiffened door (U Factor .34) in a Mercury 3 Thermal Break Frame
- First steel stiffened hollow metal swinging door to qualify for GreenGuard Gold

Strong

- Steel stiffened core for added strength and durability
- Hurricane rated up to +/-100 psf 3'0" x 7'0" single and up to +/-70 psf 8'0" x 8'0" pairs

Beautiful

- No vertical weld marks on door face sheets so aesthetically pleasing gloss paint can be applied
- Many door designs and prefinish color options available

Features and Options

Standard Features:

- 18 Gauge face sheets, 16 gauge optional
- 16 Gauge inverted end channels welded to both face sheets for added strength.
- 14 Gauge closer reinforcement

Available Sizes:

- 4'0" x 8'0" maximum single, 8'0" x 8'0" maximum pair

Material:

- Cold rolled or galvaneal steel

Core:

- 22 gauge steel stiffeners spaced every 6" apart with injected polyurethane foam

Edge Construction:


- Mechanically interlocked, hemmed vertical edge seams
- Seamless edges available


Hardware Reinforcements:

- Reinforcing for most lock preps, including concealed hardware
- 7 Gauge steel hinge reinforcements

Paint:

- Electrostatically applied prime base coat
- Optional Colorstyle factory pre-finish





Trio-E Insulated
Steel Stiffened Door

Mercury 3 Thermal Break Frame

Performance

- Thermal Insulation: U-factor of 0.34 (ASTM C1363/NFRC 102-2014) for maximum energy efficiency. The U-Factor of 0.36 and Air Infiltration (NFRC 400-2014/ASTM E283) of ≤ 0.1 cfm/ ft^2 was achieved in an operable condition using the Ceco Mercury Thermal Break Frame and Pemko Thermal Barrier Saddle. The building's actual energy performance and potential savings is a combination of the openings thermal efficiency and ability to reduce air infiltration/exfiltration.
- Physical endurance testing: Meets ANSI A250.4 performance test, level A (5,000,000 cycles) class 1 stiffness
- Hurricane rating: Up to and including +/- 100 psf 3'0" x 7'0" single or +/- 70 psf 8'0" x 8'0" pairs with weather kerf frame and cylindrical lock, mortise lock or rim exit device. U-Factor 0.38, R-Value 2.6 (NFRC 102-2014)
- Fire rating: Up to and including 3 hours 4'0" x 8'0" singles and 8'0" x 8'0" pairs (UL10C) UL & (4'0" x 8'0" singles WH 1-1/2hr max)

Ceco Door
9159 Telecom Drive • Milan, TN 38358
Tel (888) 232-6366 • Fax (888) 232-6462
archhelp@cecodoor.com
www.cecodoor.com

Experience a safer
and more open world

Ceco is a brand associated with AADG, Inc., an ASSA ABLOY Group company. Copyright © 2021, AADG, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of AADG, Inc. is prohibited.

CEC-142-06/21