

StormPro® Multi-Point Exit Tornado Resistant Assembly UL Classified to ICC500 - 2020



The new factory installed field replaceable glass option enables the glass and kit assembly to be replaced if damaged without the requirement of replacing the door. The new patented design allows for faster and less expensive repairs to the assembly if only the glass is damaged and requires replacement. This will be the standard for glazed assemblies ordered after June 7th 2023.

Ceco Door StormPro® Multi-Point Exit assemblies include glazed and flush paired openings 5'4" x 6'8" minimum through 8'0" x 8'0" maximum with a required mullion. Single glazed and flush openings are available from 3'0" x 6'8" minimum to 4'0" x 8'0" maximum. These StormPro® assemblies give end-users another option for creating highly functional safe rooms with easy means of egress.

The StormPro® Multi-Point Exit assembly helps shield occupants in a safe room from flying debris. The assemblies are UL classified to ICC-500 2020 and comply with FEMA P320 and P361. StormPro® doors are also fire rated up to and including 3 hours. As with all StormPro® products, the third party Underwriters Laboratory certification labels are applied to each assembly.

9159 Telecom Drive | Milan, TN 38358
Tel (888) 232-6366 | Fax (888) 232-6462
archhelp@cecodoor.com
www.cecodoor.com

Experience a safer
and more open world

Available Sizes:

- Pairs 5'4" x 6'8" minimum to 8'0" x 8'0" maximum
- Singles 2'8" x 6'8" minimum to 4'0" x 8'0" maximum

Frame Type:

- StormPro 14 ga. (12 ga. optional) frame single, depth thru 14" StormPro 14 gauge frame pairs, 5-1/2" depth thru 14"
- 4" head option
- Masonry or EO anchors

Door Type:

- 14 ga. (12 ga. optional) StormPro door with steel stiffened core standard (honeycomb and polystyrene core optional)

Optional Glazing:

- Factory installed field replaceable glazing available (10" x 10" or 4" x 25") with 90 minute UL certified fire rating for assemblies ordered after June 7th 2023
- See tech data for approved glass kit locations

Hardware Options:

- Multi-Point Exit Device: Corbin Russwin FE5400S
- Hardware Mullion: Corbin Russwin CRFE772A or CRFE708A Series

Hinges:

- McKINNEY SP BUTT HINGES
- MARKAR HG305, HG305WT10, FM300, FM300WT and other continuous hinges

Accessories:

- Door closers, perimeter seals, electronic power transfer, door position switches, holders/stops, viewers, rod guards and kick plates are also available

Note: Other hinges and accessories available, see tech manual.