CUT SHEET

Rockwood 2805
Self Latching Bolt
Top Bolt Only

ROCKWOOD
ASSA ABLOY

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:
Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

FASTENERS:
8 ea. #8 x 3/4" Flat Head Combo Screws.

NOTE: *No plastic anchor required.*

FEATURES:
- For Fire Rated Metal Doors labeled A, B, C, D & E up to 4'w x 8'h.
- Automatically engages when the inactive door closes. When the active door is opened, the inactive door stays latched at the top until the top bolt is released by pressing the plunger button on the bolt face.
- For Fire Rated Hollow Metal doors measuring up to 4' w x 8'h up to and including 3 hours.
- UL Listed

AVAILABLE FINISHES:
- US4/606
- US10/612
- 10BE/613E
- US32D/630
- BSP (Black Suede Powder Coat)
- BPC (Black Powder Coat)
- FBPC (Flat Black Powder Coat)
- WPC (White Powder Coat)

Size: 1" x 6 3/4"

Weight: 1.2 lbs.

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Rockwood is a brand associated with ASSA ABLOY Accessories and Door Controls Group, Inc.
Copyright © 2019-2026, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.