

Rockwood 555 x 18BFB

Lever Extension Flush Bolt with Bottom Fire Bolt

Experience a safer
and more open world



WARNING

This product can expose you to lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov.

OPTIONS:

- Other size rods available are 18", 24", 36", 48"
- Extra long bolt head - 2 1/2" (or to your specification)

SPECIFICATIONS:

MATERIAL:

- Flush Bolt - Brass
- Bottom Fire Bolt - Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

FASTENERS:

8 ea. #8 x 3/4" Flat Head Combo Screws

FEATURES:

- For Fire Rated Hollow Metal Swinging Doors measuring up to 4'w x 9'h rated up to and including 3 Hours
- Fits ANSI A115 door and frame preparation
- 3/4" bolt throw, 3/4" rod backset
- 12" rod length (center of face to bolt end - retracted)
- 1 1/2" adjustable bolt head
- When door is subjected to 230°F the plug and black plastic cover will melt allowing the bolt to project, locking the leaves together
- Bottom fire bolt eliminates need for floor prep
- Oversize fire bolt strike hole allows for slight door misalignment

AVAILABLE FINISHES:

- US26D/626

Size:

Top Bolt: 1" x 6 3/4"

Bottom Bolt: Ø 13/16"

Weight: 0.9 lbs.

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Copyright © 2019-2022, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.