

Rockwood 2949

Self Latching Flush Bolt

With Bottom Fire Bolt for Wood Doors

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

FASTENERS:

6 ea. #8 x 3/4" Flat Head Combo Screws, 2 ea. Plastic Anchors; 3 ea. #10 x 1" Flat Head Wood Screws.

FEATURES:

- Non-handed
- Low (5 lbs. maximum) closing force
- Self latching top bolt
- Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
- Wood door flush bolts cannot be extended in size. Extension rods are not available to change the overall size of the product.
- Bolt head rod is adjustable up to 1/2"
- For fire rated UL listed 20-minute wood core and composite doors up to 4'w x 9'h
- Thermal lock automatically locks the inactive door under high heat conditions due to fire
- Bottom fire bolt eliminates need for floor prep
- Oversize fire bolt strike hole allows for slight door misalignment

AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- 10BE/613E
- US32/629
- US32D/630
- BPC (Black Powder Coat)
- BSP (Black Suede Power Coat)
- FBPC (Flat Black Powder Coat)
- OptiCoat™

Size:

Top Bolt: 1" x 8 1/2"

Bottom Bolt: Ø 13/16"

Weight: 1.6 lbs.

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Rockwood is a brand associated with ASSA ABLOY Accessories and Door Controls Group, Inc.
Copyright © 2019-2026, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.