

Rockwood OH104S

Heavy Duty Overhead Stop

Concealed - Stop Only Center Hung 41 1/16" - 46"

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:
Stainless Steel

FEATURES:

- Doors may be single or double acting
- Non-handed
- Slide track design
- Recommended for high traffic, heavy abuse installations
- Heavy shock absorber spring provides 5-7° compression before deadstop
- Surface on/off knob on hold open models
- Complete screw packet for installation in wood and machine screws for door and frame
- For security areas, Torx® screws available for exposed fasteners
- Durable slider cam and shock block
- 110° maximum opening
- 1 3/4" minimum door thickness, for thicker doors, note thickness when ordering
- 1 3/16" square channel
- Stop function UL listed for fire door assemblies

FASTENERS:

Jamb: 1/4"-20 x 3/4" Flat Head Machine Screws or #14 x 1 1/2" Flat Head Wood Screws

Door: 5/16"-18 x 1 1/2" Flat Head Machine Screws or #18 x 3" Flat Head Wood Screws

OPTIONS:

- Stop Only
- Butts/Offset Pivots
38 1/16" - 43"



AVAILABLE FINISHES:

- US32D/630
- US10BE

WEIGHT:

4.5 lbs.

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Copyright © 2019-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.