

Rockwood OH204M

Standard Duty Overhead Stop

Concealed - Multi-Function - Center Hung 38 9/16" - 45"

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:
Stainless Steel

FEATURES:

- Doors may be single or double acting
- Non-handed
- Slide track design
- Recommended for medium traffic, medium weight doors
- Degree of opening is fully adjustable and can be adapted to changing needs
- Heavy shock absorber spring provides 5-7° compression before deadstop
- Multi-function unit is shipped as a stop. Can be converted to a hold open or friction in the field. MF5012 KIT (Adapter kit) included
- Complete screw packet kit for installation in wood or metal door and frame
- For security areas, Torx® screws available for exposed fasteners, but heavy-duty units should be considered for high security applications
- Durable slider cam and shock block
- 110° maximum opening
- 3/4" square channel
- Stop function UL listed for fire door assemblies

FASTENERS:

Jamb: #12-24 x 1 1/2" Flat Head Machine Screws or #12 x 1 1/2" Flat Head Wood Screws

Door: #12-24 x 1 1/2" Flat Head Machine Screws or #12 x 1 1/2" Flat Head Wood Screws

OPTIONS:

- Multi-function
- Butts/Offset Pivots
36 1/16" - 42"



AVAILABLE FINISHES:

- US32D/630
- US10BE

WEIGHT:

3.5 lbs.

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Copyright © 2019-2021, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.

OH204M-CS - 01/22