

Experience a safer
and more open world

Rockwood 307 - Non-Mortise Door Edge



Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US32D/630
- US32DMS
- US32D316

Specifications:

MATERIAL:

.050" Brass, Bronze, Stainless Steel

FASTENER:

#6 x $\frac{5}{8}$ " Flat Head Sheet Metal Screws

ORDERING:

- Specify any length up to 96" (standard lengths are 42", 84", 96")
- NOTE: 84" and 96" are made to match net door height – specify*
- Specify wood or metal door



FEATURES:

- Door Edges are sized for $1\frac{3}{4}$ " thick wood or metal doors (advise if your door is another thickness)
- NOTE: Some wood doors that are nominally $1\frac{3}{4}$ " vary significantly*

OPTIONS:

- UL fire rated listed for stainless steel, brass and bronze. For use on wood or plastic faced fire doors rated up to and including $1\frac{1}{2}$ " hours or hollow metal, steel covered, composite type fire doors rated up to and including 3 hours. Specify UL when ordering (307-UL)
- Cutouts for flush bolts, lock strikes, locks, and hinges (see worksheets on pages C10-C11 or C13-C15 for details on how to order)