

Rockwood BF169

45° Offset Door Pull

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:

Aluminum, Brass, Bronze,
Stainless Steel

FASTENER:

- 1/4"-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

OPTIONS:

- Back to back mounting in pairs — use BTB suffix and mounting type number (BF169BTB16)
- Concealed mounting single pulls — use C suffix and mounting type number (BF169C17)
- Advise if door thickness is other than 1 3/4"
- Heavy duty versions of most fastening types available — use suffix HD to fastening type number (BF169BTB16HD)
- Use Y prefix (YBF169) when ordering pulls with base plates, Y plate diameter is 1 1/16"; recommended for use on wood and glass doors

AVAILABLE FINISHES:

- US28/628
- 313/710
- 315/711
- US3/605
- US4/606
- US10/612
- US10B/613
- 10BE/613E
- US26/625
- US26D/626
- US32D/630
- US32/629
- US32DMS
- US32D316
- US32316
- US32MS
- BPC (Black Powder Coat)
- BSP (Black Suede Powder Coat)
- FBPC (Flat Black Powder Coat)
- WPC (White Powder Coat)
- WSP (White Suede Powder Coat)
- RPC (Red Powder Coat)
- OptiCoat™

Material Size: 3/4" dia.

CTC: 5 1/2" – 18" (Standard 18")

Base: 1"

Projection: 3 1/2"

Clearance: 2 1/2"

Offset: 2 3/4"

Weight: 5.0 lbs.

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424