Architectural Door Accessories

ASSA ABLOY

Pemko Perimeter Gasketing

The global leader in door opening solutions


Applies to the following products:

379_S, 379_R

Installation Instructions:

1. Can be installed on a wood or metal frame.
2. Measure, mark and trim piece to length. Close door and position so that seal makes light even contact with door. Mark in center of holes.
3. Drill pilot holes in stop at marks.
4. Secure piece to stop with supplied screws.
5. Open and close door several times to check jamb weatherstrip fit and seal.
6. Adjust the adjustment screw as necessary to fit seal properly.

Tools Required:



Testing/Ratings:

Gasketing material for fire doors intended for aplication to listed steel frames and/or classified steel covered composite type, and hollow metal type fire doors rated up to 3 hours; wood and plastic covered composite type fire doors rated up to 1-1/2 hours; and wood core type fire doors rated up to 20 minutes.
(Thresholds may or may not contain gasketing material).

10C

BHMA CERTIFIED

CLASSIFIED C UL US 4L10

www.pemko.com

MEMPHIS, TN USA
P: 800 824-3018
F: 800 243-3656

VENTURA, CA USA
P: 800 283-9988
F: 800 283-4050

VANCOUVER, BC CA
P: 877 535-7888
F: 877 535-7444

TORONTO, ON CA
P: 877 535-7888
F: 877 535-7444

Copyright © 2017 Pemko Manufacturing Co., an ASSA ABLOY Group company. All rights reserved.
Reproduction in whole or in part without the express written permission of Pemko Manufacturing Company is prohibited.