

## Door Rails Order Form

Experience a safer  
and more open world

Complete this form and email / fax to: Orders.GlassSolutions@assaabloy.com / 844.851.8665

## Customer Information

Contact Name: \_\_\_\_\_ Date: \_\_\_\_\_  
Company Name: \_\_\_\_\_ PO #: \_\_\_\_\_  
Street Address: \_\_\_\_\_ Phone/Fax: \_\_\_\_\_ / \_\_\_\_\_  
City/State/Zip: \_\_\_\_\_ Email: \_\_\_\_\_  
Architect Name: \_\_\_\_\_ Job Name and Location: \_\_\_\_\_

Quote #: \_\_\_\_\_

Glass Thickness: ☐ 1/2" ☐ 9/16" ☐ 5/8" ☐ 11/16" ☐ 3/4"Finish: ☐ US32D/630 ☐ US32/629 ☐ US28/628 ☐ 314 ☐ 314E  
☐ BSP ☐ WSP ☐ 4E ☐ Other \_\_\_\_\_Pivot Centerline from End Cap: ☐ 2 5/8" ☐ 3 1/2" ☐ Other \_\_\_\_\_Vertical Styles: ☐ Length \_\_\_\_\_ Pile Height: ☐ 3/16" (Std) ☐ 3/8" ☐ Flat Vinyl

## Top Rail Height

Standard: ☐ 4" Square ☐ 4" Tapered ☐ 6" Square ☐ 10" Square  
Low Profile: ☐ 2 3/4" Square ☐ 2 3/4" Tapered

## Top Rail Hardware Preps

Closer: ☐ OHC-609 / OHC-304 / RTS88 ☐ \*Other \_\_\_\_\_  
Pivot: ☐ PV-Walkbeam ☐ PV-340 ☐ Rixson 180 ☐ \*Other \_\_\_\_\_  
Panic/Dummy Panic: ☐ Part # \_\_\_\_\_ (Standard Backset 4 1/8")  
Electrical: ☐ Mag-SAM ☐ Mag-SAM2 ☐ \*Other \_\_\_\_\_  
Auto Operator: ☐ Model # \_\_\_\_\_  
Weatherstrip: ☐ Prep & Install Top Rail  
Pull Prep: \*\*Hole Prep: ☐ Through Rail ☐ One Side ☐ Interior ☐ Exterior  
Location: ☐ 1 1/8" Down; \_\_\_\_\_ Backset ☐ Other Hole Size \_\_\_\_\_  
\*\*Standard RM pull prep is 1 1/32". \*\*\*If backset not completed we will assume 4 1/8".  
\*Other: ☐ \_\_\_\_\_ ☐ Location \_\_\_\_\_

\*Templates required for all hardware not listed in Glass Solutions Price Book.

page 1 of 2

The ASSA ABLOY Group is the global leader in access solutions. Every day we help people feel safe, secure and experience a more open world.

### Bottom Rail Height

Standard: ☐ 4" Square ☐ 4" Tapered ☐ 6" Square ☐ 10" Square  
Low Profile: ☐ 2 3/4" Square ☐ 2 3/4" Tapered

### Bottom Rail Hardware Preps

Closer: ☐ FC-6280/6275 ☐ FC-28 ☐ Undercut: \_\_\_\_\_  
☐ Straight Arm ☐ Offset Arm ☐ 28 Arm ☐ 554 Arm  
Pivot: ☐ PV-Endload ☐ PV-300 End Load ☐ \*Other: \_\_\_\_\_  
Panic/Dummy Panic: ☐ Part # \_\_\_\_\_ (Standard Backset 4 1/8")  
Lock: ☐ CYL/CYL ☐ CYL/TT ☐ CYL/TT by Others ☐ 570 Dustproof Strike ☐ Indicator  
Auto Operator: ☐ Model # \_\_\_\_\_  
Weatherstrip: ☐ Prep & Install Bottom Rail  
Pull Prep: \*\*Hole Prep: ☐ Through Rail ☐ One Side ☐ Interior ☐ Exterior  
Location: ☐ 1 1/8" Up; \_\_\_\_\_ Backset ☐ Other Hole Size \_\_\_\_\_  
\*\*Standard RM pull prep is 1 1/32". \*\*\*If backset not completed we will assume 4 1/8".  
\*Other: ☐ \_\_\_\_\_ ☐ Location \_\_\_\_\_

\*Templates required for all hardware not listed in Glass Solutions Price Book.

### Configuration:

Quantity	Top/Bottom	Length	Door Opening	Swing	Door Mark
1	T	35 3/4"	36"	3	A

Customer Signoff: \_\_\_\_\_ Date: \_\_\_\_\_

### Custom Instructions and Other Hardware Specify Below:

### Door Swings:

