



Hurricane

DESIGN PRESSURE +/- 70 PSF
IMPACT RATING 350 FT. LBS.

**PRODUCT QUALIFIED FOR USE IN HIGH VELOCITY HURRICANE ZONE (HVHZ)
(HVHZ-BROWARD AND MIAMI DADE COUNTIES)**

TEST STANDARDS

| | |
|------|--------------------|
| ANSI | A250.13 |
| ASTM | E330, E1886, E1996 |
| TAS | 201, 202, 203 |

FRAMES - UL-FL 11537 WHI - FL 8768

| | |
|----------------|--|
| DESCRIPTION | 3F |
| CCW | N/A |
| LABEL | IF FIRE LABEL IS NEEDED THE FIRE AGENCY AND WIND AGENCY MUST BE THE SAME UL OR WHI WINDSTORM LABEL REQUIRED, MAY BE FIRE RATED UP TO 180 MINUTES |
| JAMB DEPTH | 5-3/4" MINIMUM - 14" MAXIMUM |
| PROFILE TYPE | M, G (2-5/8" FACE ON F2), B, L, LG, 300, 301, 303 (2-13-16" FACE), AND BG 2" FACE ONLY |
| STEEL GAUGE | 16 AND 14 |
| STEEL TYPE | COLD ROLLED, GALVANEAL, G90, STAINLESS STEEL |
| CONSTRUCTION | KD - WELDED AT FACTORY, DOOR GROUP SERVICE CENTER OR APPROVED WINDSTORM SECOND LOCATION |
| HAND | IN SWING AND OUT SWING |
| ACTIVE LEAF | N/A |
| ANCHORS | MASONRY T, MASONRY WIRE, OR WELDED TO BUILDING STRUCTURE WELDED PIPE SPACER, WELDED WOOD STUD OR WELDED EXISTING WALL ANCHOR - WOOD STUD WALL WELDED PIPE SPACER OR WELDED EXISTING WALL ANCHOR - MASONRY WALL WELDED MULTI-PURPOSE ANCHOR OR WELDED STEEL CHANNEL ANCHOR - METAL STUD WALL |
| OVERALL WIDTH | 40" OR SMALLER |
| OVERALL HEIGHT | 88" OR SMALLER |
| DOUBLE OPENING | N/A |
| 4" FACE HEAD | ALLOWED - OVERALL HEIGHT 88" |
| MFG LOCATIONS | ANY SDI MEMBERS COMPANY LOCATIONS |
| STRIKES | E-1, E-1/E-4, E-2/E-2, AND E-2/E-4 |
| DUTCH FRAME | N/A |
| SILENCERS | ALLOWED |
| SPECIAL INST. | MAY USE READYSET MUST BE WELDED AT FACTORY ONLY |

DOORS - UL-FL 11537 WHI - FL 8768 - FIRE RATED VISION LIGHT KIT AND GLASS WHI - FL 12537

| | |
|-----------|---|
| FACE TYPE | NON FIRE RATED FLUSH OR GLAZED MAXIMUM VISIBLE WIDTH 24", MAX HEIGHT 42", MAXIMUM VISIBLE AREA 1,008 SQ. IN. 6" MINIMUM STILE AND RAIL DIMENSION REQUIRED. MULTIPLE LIGHTS ALLOWED FIRE RATED FLUSH, 180 MINUTES UNDERWRITERS LABORATORIES OR WARNOCK HERSEY GLAZED, 90 MINUTES WARNOCK HERSEY VISIBLE WIDTH 23", MAX. HEIGHT 53", MAXIMUM AREA 1,219 IN. 6" MINIMUM STILE AND RAIL DIMENSION REQUIRED. MULTIPLE LIGHTS ALLOWED |
| LOUVERS | MAXIMUM WIDTH 24" MAXIMUM HEIGHT 78" MAXIMUM SQ. IN. 1,872 NOTE: FIRE RATED LOUVERS MAY BE USED PROVIDED THEY ARE ALSO IMPACT RATED |
| LABEL | IF FIRE LABEL IS NEEDED THE FIRE AGENCY AND WIND AGENCY MUST BE THE SAME UL OR WHI WINDSTORM LABEL REQUIRED; UL OR WHI FIRE LABEL AS DESCRIBED IN FACE TYPE |

Continued on Page 2



Hurricane

DESIGN PRESSURE +/- 70 PSF

IMPACT RATING 350 FT. LBS.

PRODUCT QUALIFIED FOR USE IN HIGH VELOCITY HURRICANE ZONE (HVHZ)
(HVHZ-BROWARD AND MIAMI DADE COUNTIES)

DOORS - UL-FL 11537 WHI - FL 8768 - FIRE RATED VISION LIGHT KIT AND GLASS WHI - FL 12537 (continued)

| | |
|----------------|---|
| DOOR SERIES | 607, 707, 707 EMBOSSED, 707 CURRISTAIN, 727, AND 747 |
| DOOR EDGE | S, N, T, WELD |
| STEEL GAUGE | 607 - 18 707 AND 747 - 18, 16, AND 14 727 - 18 AND 16 |
| STEEL TYPE | 607 - CR 707, 727, 747 - COLD ROLLED, GALVANEALD, AND G90 EMBOSSED, AND CURRISTAIN; STAINLESS STEEL 16 GAUGE 707 ONLY |
| BEVEL | A, B, OR G |
| TOP CAP | OPTIONAL |
| HAND | IN SWING AND OUT SWING |
| WIDTH | 3'0" OR SMALLER |
| HEIGHT | 7'0" OR SMALLER |
| DOOR THICKNESS | 1-3/4" ONLY |
| LOCK PREPS | G3, G3A, G3AEO, G2/G2, G2B/G2, G2/G17, G2B/G17, AND G25. ALL AT 2-3/4" BACKSET |
| UNDERCUT | 3/4" MAXIMUM |
| ASTRAGAL | N/A |

HARDWARE

| | |
|------------------|---|
| HINGES | U453, 453, H453, 503, H503 MCKINNEY: CONTINUOUS HINGES: MCK-12 HD, MCK-14HD, MCK-25HD, MCK-FM300, MCK-FM3500, MCK-FM3700, AND MCK-HG305 MARKAR: CONTINUOUS HINGES: FM100, FM200, FM300, FM3500, FM100, FM1111, AND HG300 RIXON: PIVOTS: 195 TOP AND BOTTOM PIVOT SET WITH M19 INTERMEDIATE PIVOTS |
| LOCKS | MORTISE LOCK WITH DEAD BOLT AND LATCH BOLT CYLINDRICAL LOCK WITH CYLINDRICAL DEAD BOLT INTERCONNECTED LOCK CORBIN RUSSWIN: CYLINDRICAL LOCK: CL3300 SERIES WITH DL3100 SERIES DEAD BOLT MORTISE LOCK: ML2000 SERIES WITH LATCH BOLT AND DEAD BOLT SARGENT: CYLINDRICAL LOCK: 10 LINE SERIES WITH 480 SERIES DEAD BOLT MORTISE LOCK: 7800, 8200, 8200 PROFILE SERIES WITH LATCH BOLT AND DEAD BOLT SECURITRON: POWER TRANSFER: EPT; EPTL, CEPT ASSA ABLOY ACCENTRA: CYLINDRICAL LOCK: 5400/5400LN SERIES WITH 3600 SERIES DEAD BOLT INTERCONNECTED LOCK: 4800 SERIES MORTISE LOCK: 8800 SERIES WITH LATCH BOLT AND DEAD BOLT |
| HARDWARE MULLION | NOT ALLOWED |
| CLOSER | CLOSERS ALLOWED - NO CONCEALED CLOSERS OR HOLDERS ALLOWED |
| NOTE | OTHER APPROVED HARDWARE MAY BE USED |