



NOTES:

- Do not scale drawing.
- Left hand door shown.
- Dimensions are given in inches (mm).
- Hollow metal doors require channel or box-type reinforcement.
- Hollow metal frames require full width header reinforcement.
- The UNITJ4410 model door closer has a hole open arm feature that is not permitted for use on fire door assemblies.

Preparation for Fasteners			
Fasteners	To Apply	Door or Frame	Drill Sizes
Sex nuts and bolts	Arm Foot	Hollow-Metal	9/32" (7.00mm) through 3/8" (9.50mm) door-face opposite to closer
		Aluminum or Wood	3/8" (9.50mm) through
#14 x 1/4" (32mm) type "A" S.M. screw	486 Closer Backplate	Wood	7/32" (5.5mm)
		Metal	drill: #7 (.201" dia.) tap: 1/4-20
1/4-20 machine screw		All	9/32" (7.00mm) through; 3/8" (9.50mm) dia. x 3/8" (10mm) deep, door face opposite to closer
Thru bolts and grommet nuts	Optional		

Door Opening Angle		Dimensions	
Hold Open	Dead Stop	Butts and Offset Pivots	Center Pivots
		Dimension A	Dimension A
85°	90°	9-3/4 (248)	10-1/4 (260)
90°	95°	9-1/8 (232)	9-5/8 (244)
95°	100°	8-1/2 (216)	9-1/8 (232)
100°	105°	8 (203)	8-5/8 (219)
105°	110°	7-3/4 (197)	8-1/8 (206)
110°	115°	7-3/8 (187)	7-7/8 (200)

4400 Series Door Closer
Models UNIJ4400, UNIJ4410 With 486 Back Plate
Non-Hold Open or Hold Open; UNI Stop™ Top Jamb, With 589L Bracket

ACCENTRA
ASSA ABLOY

TEMPLATE NUMBER	7344-1401	REV	3	DATE	05/24
-----------------	-----------	-----	---	------	-------